

Packaging

12x1kg
PACKAGING



4x4kg
PACKAGING



15kg
PACKAGING



180kg
PACKAGING



Product	NLGI Grade	Specification	Product Description
ZNOIL GRL	NLGI 00	DIN 51502 KP00K-30, ISO 6743-9 L-X-CCEB-00	High-performance semi-fluid grease designed for automotive centralized lubrication systems, offering excellent pumpability and reliable lubrication performance.
ZNOIL GRL	NLGI 00	DIN 51502 GP00K-20, ISO 6743-9	Semi-fluid grease developed for cotton harvesting machines, providing smooth operation and excellent pumpability in lubrication systems.
ZNOIL GRL	NLGI 1 / 2 / 3	DIN 51502, ISO 6743-9 L-X-CCHA	Multi-purpose lithium grease with anti-wear properties, suitable for general automotive and industrial lubrication applications.
ZNOIL GRL	NLGI 00 / 0 / 1 / 2 / 3	DIN 51502, ISO 6743-9 L-X-CCEB	Lithium-based EP grease designed for industrial, agricultural, and automotive applications, providing excellent load protection and lubrication performance.
ZNOIL GRL	NLGI 2	DIN 51502 OGFP2K-30	Lithium grease with graphite additives designed for open gears and exposed surfaces, offering excellent adhesion and wear protection.
ZNOIL GRL	NLGI 2	DIN 51502 KPF2K-30	Lithium grease with molybdenum disulfide (MoS ₂) for vehicles and off-road equipment, providing enhanced protection under vibration and heavy loads.
ZNOIL GRL	NLGI 2 / 3	DIN 51502 K2G-20 / K3G-20	Calcium-based grease offering excellent adhesion, water resistance, and reliable lubrication for chassis, agricultural machinery, and general applications.
ZNOIL GRL	NLGI 2	DIN 51502 K2G-20	Graphite-enhanced calcium grease providing reliable protection against wear, metal contact, corrosion, and heavy-duty operating conditions.
ZNOIL GRL	NLGI 1 / 1-2 / 2 / 3	DIN 51502, ISO 6743-9 L-X-BFIB	Advanced calcium sulfonate complex grease offering excellent EP protection, mechanical stability, thermal resistance, and superior water resistance.
ZNOIL GRL	NLGI 1-2 / 2	DIN 51502, ISO 6743-9 L-X-BFIB	Premium calcium sulfonate complex grease providing outstanding load protection, water resistance, oxidation stability, and long service life.
ZNOIL GRL	NLGI 1/2	DIN 51502, ISO 6743-9	High-performance lubricant for hydraulic breakers, with advanced calcium sulfonate complex thickener. Offers mechanical stability, water and corrosion resistance, and extreme pressure performance. Enriched with copper and graphite to prevent metal-to-metal contact. Range: -20°C/+200°C, protection up to 1100°C.

Packaging

12x1kg
PACKAGING



4x4kg
PACKAGING



15kg
PACKAGING



180kg
PACKAGING



Product	NLGI Grade	Specification	Product Description
ZNOIL GRL	NLGI 2	DIN 51502 KPF2P-30, ISO 6743-9 L-X-CEHB-2	Heavy-duty lithium complex EP grease with MoS ₂ designed for heavily loaded bearings, providing excellent shock load protection, mechanical stability, and water resistance.
ZNOIL GRL	NLGI 2 / 3	DIN 51825/51502, ISO 6743-9 L-X-BEHB-2/3	Heavy-duty lithium complex EP grease with high viscosity base oils, offering excellent load protection, mechanical stability, and water resistance for demanding applications.
ZNOIL GRL	NLGI 2	DIN 51502 KPF2P-20, ISO 6743-9 L-X-BE-2	High-performance lithium complex grease with MoS ₂ , providing excellent adhesion, structural stability, and protection against shock loads.
ZNOIL GRL	NLGI 0/00	DIN 51502 OGP 0/00 N-10, ISO 6743-9 L-X-ADHB 0/00	Heavy-duty tacky semi-fluid graphite grease designed for open gears and shock-loaded applications, offering excellent wear protection and water resistance.
ZNOIL GRL	NLGI 1 / 2 / 3	DIN 51502, ISO 6743-9 L-X-BCHB1/2/3	Water-resistant lithium-calcium EP grease suitable for bearings and equipment operating in wet environments, including agricultural and construction machinery.
ZNOIL GRL	NLGI 2	DIN 51502 K2K-20, ISO 6743-9 L-X-BCHA-2	Multi-purpose lithium-calcium grease with anti-wear properties, designed for general automotive, industrial, and construction equipment applications.
ZNOIL GRL	NLGI 2	DIN 5102 K2R-20, ISO 6743-9 L-X-BFAA2	High-temperature bentonite grease offering excellent oxidation stability, low volatility, and reliable lubrication in elevated temperature applications.
ZNOIL GRL	NLGI 2	—	Anti-seize compound with copper and graphite additives designed for threaded connections, preventing seizure and reducing dismantling effort in automotive and industrial applications.
ZNOIL GRL	NLGI 2	DIN 51502 KP2P-20, ISO 6743-9 L-X-BEHB-2	High-performance polyurea grease designed for heavily loaded rolling bearings in severe industrial applications, offering excellent EP protection, oxidation stability, and corrosion resistance.
ZNOIL GRL	NLGI 2	DIN 51502 KP HC 2P-40, ISO 6743-9 L-X-DEEB2	Premium PAO-based synthetic lithium complex grease providing excellent low-temperature performance, thermal stability, wear protection, and reduced friction.
ZNOIL GRL	NLGI 2	NSF Cat. H1 Reg. Nr 161278, DIN 51502, KP2N-20, ISO 6743-9 L-X-BDEB2	Food-grade aluminium complex grease formulated with high-purity oils, offering excellent wear protection, oxidation stability, and reliable performance in food processing applications.