

Packaging

12x1L



4x4L



4x5L



20L



208L



1000L



Product	ISO VG	Specification	Product Description
ZNOIL IML	ISO 10 / 22 / 32 / 46 / 68 / 100	ISO 6743-4 L-HM, ISO 11158 (CETOP RP 91H) HM, DIN 51524 Part 2 HLP	High-performance anti-wear hydraulic fluids providing excellent protection, oxidation stability, and wear resistance for industrial, marine, and mobile hydraulic systems.
ZNOIL IML	ISO 15 / 22 / 32 / 46 / 68 / 100 / 150	DIN 51524 Part 3 HVLP, ISO 6743-4 L-HV, AFNOR NF E48-603 HV	High viscosity index hydraulic fluids designed for stable performance under temperature variations and heavy-duty operating conditions.
ZNOIL IML	ISO 32	DIN 51517-3 CLP, ISO 6743-6 (ISO-L-CKC)	Extreme pressure industrial lubricant designed for gear systems, offering excellent load carrying capacity, oxidation stability, and corrosion protection.
ZNOIL IML	ISO 46 / 68	ISO 6743/4 HM, DIN 51524 Part 2 HLP, AFNOR NFE-48603 HM	Zinc-free anti-wear hydraulic fluids providing reliable performance, wear protection, and thermal stability in demanding hydraulic applications.
ZNOIL IML	ISO 46	ISO 6743-4 L-HFC	Fire-resistant water-glycol hydraulic fluid offering excellent safety, wear protection, and corrosion resistance in high-risk applications.
ZNOIL IML	ISO 46 / 68	ISO 6743-4 L-HFDU	Environmentally friendly synthetic ester-based fire-resistant hydraulic fluid designed for reliable performance in demanding conditions.
ZNOIL IML	ISO 68 / 100	DIN 51506 VDL, ISO 6743-3 (ISO-L-DAA/ISO-L-DAB)	Synthetic ester-based compressor lubricants providing excellent wear protection, water separation, and performance in high-pressure compressors.
ZNOIL IML	ISO 68 / 150 / 220	—	Synthetic polyglycol-based compressor lubricants designed for gas compressors handling LPG, LNG, and industrial process gases.
ZNOIL IML	ISO 32 / 46 / 68 / 100	DIN 51506 VDL, ISO 6743-3 (ISO-L-DAJ)	Synthetic PAO-based compressor oils offering excellent oxidation stability, wear protection, and extended drain intervals.
ZNOIL IML	ISO 32 / 46 / 68 / 100 / 150 / 220	DIN 51506 VDL, ISO 6743-3 (ISO-L-DAH)	Zinc-free mineral compressor lubricants designed for reliable wear protection and deposit control in rotary, vane, and screw compressors.

Packaging

12x1L



4x4L



4x5L



20L



208L



1000L



Product	ISO VG	Specification	Product Description
ZNOIL IML	ISO 150 / 220 / 320 / 460	DIN 51517 Part 3 CLP PG, ISO 12925-1 CKE, ISO 6743-6-L-CKE, ANSI/AGMA 9005-E02 Flender	Synthetic polyglycol-based industrial gear lubricants offering extended drain intervals, energy efficiency, micropitting resistance, and excellent protection under high loads.
ZNOIL IML	ISO 68 / 150 / 220 / 320 / 460	DIN 51517 Part 3 CLP, U.S. Steel 224, AGMA 9005-E02: EP, ISO 12925-1 CKD (ISO 6743-6-L-CKD), Flender	Synthetic PAO-based industrial gear lubricants providing excellent oxidation stability, micropitting protection, extended service life, and high load performance.
ZNOIL IML	ISO 68 / 100 / 150 / 220 / 320 / 460 / 680 / 1000	DIN 51517 Part 3 CLP, U.S. Steel 224, AGMA 9005-E02: EP, ISO 12925-1 CKC (ISO 6743-6-L-CKC), Flender AG	Mineral extreme pressure (EP) gear lubricants designed for heavy-duty industrial gearboxes and bearings, offering excellent wear, corrosion protection, and load-carrying performance.
ZNOIL IML	ISO 32 / 46 / 68 / 100 / 150 / 220 / 320 / 460 / 680	DIN 51517 Part 3 CLP, U.S. Steel 224, AGMA 9005-E02: EP, ISO 12925-1 CKC (ISO 6743-6-L-CKC), Flender AG	Mineral industrial lubricants suitable for gearboxes, circulation systems, vacuum pumps, and general lubrication applications requiring reliable protection.
ZNOIL IML	—	ISO-L-MAB	Synthetic metalworking fluid forming a stable microemulsion with water, designed for machining, cutting, drilling, and grinding operations with excellent lubricity and tool protection.
ZNOIL IML	—	ISO-L-MAB	Semi-synthetic water-soluble cutting and grinding fluid offering long service life, high machining performance, and suitability for various metalworking operations.
ZNOIL IML	—	ISO-L-MAB	High-performance synthetic metalworking fluid for grinding and machining ferrous and non-ferrous materials, offering excellent stability and bacterial resistance.
ZNOIL IML	—	ISO-L-MAB	Synthetic metal forming fluid designed for tube forming and shaping operations, providing excellent lubrication and protection while being chlorine and amine free.
ZNOIL IML	—	ISO-L-MAB	Mineral metalworking fluid designed to form stable milky emulsions when mixed with water. It has good bacteria resistance. Suitable for all kinds of metalworking operations. Dilution concentrations 3-10%.

Packaging

12x1L



4x4L



4x5L



20L



208L



1000L



Product	ISO VG	Specification	Product Description
ZNOIL IML	—	ISO-L-MAB	Water-repellent rust preventive fluid designed for medium-term corrosion protection of metal surfaces during storage and handling.
ZNOIL IML	—	ISO-L-MAB	Long-term rust preventive fluid forming a protective wax film after solvent evaporation for enhanced corrosion protection of metal surfaces.
ZNOIL IML	—	ISO-L-MAE	High-performance anti-corrosion fluid forming a protective soap-type film, designed for long-term storage protection of metal surfaces.
ZNOIL IML	ISO 22 / 32	ISO 6743-7 (ISO-L-MHD)	High-quality neat cutting oils for machining ferrous and non-ferrous metals, providing excellent tool protection, lubrication, and corrosion resistance.
ZNOIL IML	—	ISO-L-MAF	Low-viscosity, high-purity fluid with high flash point, designed for metalworking, aluminium foil finishing, and EDM applications.
ZNOIL IML	—	ISO-L-MAF	High-purity stamping fluid designed for metal forming applications, providing excellent lubrication for steel, galvanized steel, and yellow metals.
ZNOIL IML	ISO 40 / 68 / 100	ISO 6743-11 PAC/PBC	Mineral lubricants for pneumatic and rock drilling tools, providing strong oil film protection, wear resistance, and corrosion protection under demanding conditions.
ZNOIL IML	ISO 22 / 32	ISO 6743-1 L-CKC	Special mineral lubricants for knitting, sewing, and textile machinery, offering oxidation stability, non-drip performance, and easy cleaning properties.
ZNOIL IML	LD / MD	—	Low-viscosity mould release fluids designed to provide easy separation of concrete from metal, wood, and plastic mould surfaces.
ZNOIL IML	ISO 68 / 220 / 320 / 460	ISO 6743-11 PAC/PBC	High performance mineral lubricants with adhesion additives for the lubrication of industrial slideways. They offer excellent separation from cutting emulsions, superior frictional performance and high antiwear and anti-corrosion behaviour.
ZNOIL IML	ISO 32 / 46 / 68 / 100	DIN 51515 Part 1 L-TD & Part 2 L-TG, ISO L-TGA (ISO 8068:2019)	Mineral lubricants with excellent demulsifying properties, for steam and light duty gas turbines. They offer excellent rust and corrosion protection, and superior oxidation stability.

Packaging

12x1L



4x4L



4x5L



20L



208L



1000L



Product	ISO VG	Specification	Product Description
ZNOIL IML	Grade A	ISO 6743-12 L-QC	High quality oils for heat transfer systems operating between 10°C and 320°C. They have high thermal conductivity and oxidation resistance.
ZNOIL IML	—	ISO 6743-1 ISO-L-AC	High quality, solvent based lubricant for industrial drive and transport chains. It contains special soap and polymer type additives for effective lubrication and anti-wear protection.
ZNOIL IML	—	ISO 6743-1 ISO-L-AC	High performance synthetic ester based, chain lubricant designed for lubrication of high temperature conveyor chains at temperatures up to 290°C. It is suitable for use in fiber glass, particle board production etc. It offers high anti-wear protection, low deposit formation and reduced lubricant consumption.
ZNOIL IML	ISO 22 / 32	—	High quality paraffinic mineral lubricants blended with special additives for steel quenching in oil baths operating at temperatures between 20°C and 60°C. They ensure minimum deformation and decoloration.
ZNOIL IML	—	IEC 60296: 2020 Edition 5	Inhibited electrical insulating oil produced from severely hydrotreated naphthenic base oils meeting IEC 60296-2012 Edition 4.0 Standard table-2 General Specifications. It has excellent dielectric strength, low temperature performance, and cooling properties.
ZNOIL IML	ISO 46 / 68	NSF Cat. H1 Reg. Nr 164562/164563, DIN 51524 HLP, ISO 6743-4 HM	High performance, non-toxic, hydraulic lubricants designed for use in equipment for processing and packaging of food, beverages and pharmaceuticals. The FG HYDRO series is based on a selection of suitable base oils and special additives in order to meet the strict requirements of the food industry.
ZNOIL IML	ISO 220 / 320	NSF Cat. H1 Reg. Nr 164564/164565	Synthetic, non-toxic, PAO based industrial gear lubricants designed for use in equipment for processing and packaging of food, beverages and pharmaceuticals. They offer long drain intervals, resistance to micropitting, oxidation stability at elevated temperatures, and excellent protection at high load conditions.
ZNOIL IML	ISO 46 / 100	NSF Cat. H1 Reg. Nr 164566/164567	Synthetic, non-toxic, PAO based compressor lubricants designed for use in equipment for processing and packaging of food, beverages and pharmaceuticals. They are formulated with selected additives in order to meet the strict requirements of the food industry.